



PRODUCT SPECIFICATIONS

| | |
|--------------------|----------------------------------|
| Size | 9" x 72" |
| Thickness | 5.5 mm |
| Wear Layer | 20 mil |
| Finish | ArmourGuard Microbead Technology |
| Attached Pad | QuietStep Cushion + |
| Core | TriCore ESPC |
| Micro Beveled Edge | Yes |
| Traffic Use | Light Commercial |
| Installation | Floating Click |
| Pieces Per Carton | 8 |
| SF Per Carton | 36.64 |
| Cartons Per Pallet | 48 |
| SF Per Pallet | 1,758.52 |

WARRANTY

15 Year Light Commercial / Limited Residential Lifetime

PERFORMANCE

| | |
|----------------------------------|--|
| ASTM F2055 Size | Pass |
| ASTM F386 Thickness | Pass |
| ASTM F2055 Squareness | Pass |
| ASTM F1914 Residual Indentation | Pass |
| ASTM F137 Flexibility | Pass |
| ASTM F2199 Dimensional Stability | Pass |
| ASTM F925 Chemical Resistance | Pass |
| ASTM F1514 Resistance to Heat | Pass |
| ASTM F1515 Resistance to Light | Pass |
| ASTM F 970 Static Load Limit | Pass |
| Certified Low Emitting Product | Meets Guidelines |
| Indoor Air Quality | Meets Guidelines |
| Indoor Sound Transmission Test | IIC: 68 (test condition: 6" concrete slab with drop ceiling) |

